

PREMAX FTPI

| PLATE CAPACITY | | CONVEYOR SPEED | AVERAGE WATER CONSUMPTION | ENERGY CONSUMPTION in kWh ^[2] | RECOMMENDED MODEL SELECTION | TOTAL LENGTH | ENTRY ZONE | EXIT ZONE |
|----------------------------|----------|----------------|---------------------------|---|-----------------------------|--------------|------------|-----------|
| acc. to DIN ^[3] | maxi-mum | in m/min | in l/h ^[1] | (connected load in kW) with CLIMATE-PLUS energy saving system ^[4] | | in mm | in mm | in mm |
| 2,840 | 3,490 | 1.30 | 130 | 15.2 (25.3) | FTPi 0-L-A-R-DL3 | 4,850 | 440 | 800 |
| | | | | | FTPi 0-L-A-R-DL4 | 5,150 | 440 | 1,100 |
| | | | | | FTPi 1-L-A-R-DL3 | 5,150 | 740 | 800 |
| | | | | | FTPi 1-L-A-R-DL4 | 5,450 | 740 | 1,100 |
| 2,840 | 3,490 | 1.30 | 130 | 15.2 (25.3) | FTPi 0-L-A-R-DS4 | 5,150 | 440 | 800 |
| | | | | | FTPi 0-L-A-R-DS5 | 5,450 | 440 | 1,100 |
| | | | | | FTPi 1-L-A-R-DS4 | 5,450 | 740 | 800 |
| | | | | | FTPi 1-L-A-R-DS5 | 5,750 | 740 | 1,100 |
| 3,380 | 4,030 | 1.55 | 130 | 15.2 (25.3) | FTPi 1-S-A-R-DS4 | 5,450 | 440 | 800 |
| | | | | | FTPi 1-S-A-R-DS5 | 5,750 | 440 | 1,100 |
| | | | | | FTPi 2-S-A-R-DS5 | 6,050 | 740 | 1,100 |
| | | | | | FTPi 2-S-A-R-DS6 | 6,350 | 740 | 1,400 |
| 3,710 | 5,450 | 1.70 | 130 | 14.8 (25.3) | FTPi 1-E-S-A-R-DS5 | 6,250 | 440 | 1,100 |
| | | | | | FTPi 2-E-S-A-R-DS5 | 6,550 | 740 | 1,100 |
| | | | | | FTPi 2-E-S-A-R-DS6 | 6,850 | 740 | 1,400 |
| | | | | | FTPi 2-E-S-A-R-DS7 | 7,150 | 740 | 1,700 |
| 4,320 | 5,800 | 1.98 | 150 | 20.1 (34.3) | FTPi 2-S-D-A-R-DS5 | 6,550 | 740 | 1,100 |
| | | | | | FTPi 2-S-D-A-R-DS6 | 6,850 | 740 | 1,400 |
| | | | | | FTPi 2-S-D-A-R-DS7 | 7,150 | 740 | 1,700 |
| 5,240 | 7,420 | 2.40 | 160 | 21.9 (37.3) | FTPi 2-S-A-A-R-DS5 | 6,950 | 740 | 1,100 |
| | | | | | FTPi 2-S-A-A-R-DS6 | 7,250 | 740 | 1,400 |
| | | | | | FTPi 2-S-A-A-R-DS7 | 7,550 | 740 | 1,700 |

All values are for machines with a passage width of 612 mm.

^[1] Fresh-water consumption values under optimised conditions and in **PREMAX** models using the SENSOTRONIC system (different customer-specific values are possible).

^[2] Average value for exemplary tableware and operation type.

^[3] For hygienic rinse result according to DIN SPEC 10534

^[4] Machines with heat pump contain up to 5.1 kg (3.22 t CO₂-equivalent) of the refrigerant R531A (GWP 631)