



HOBART

GENERAL LEGEND

AW	=	drain water	KW	=	cold water	AFFL	=	above finished floor level
Dat	=	dataline	KWw	=	cold water soft	SFB	=	separate filling-boiler
EZ	=	power line (supply)	LR	=	conduit Ø	VEW	=	demineralized water
FD	=	floor opening	CNS	=	stainless steel (inox)	WD	=	wall opening
HW-VL	=	hot water flow	MK	=	supply channell	WS	=	wall slot
HW-RL	=	hot water return	PA	=	equipotential conductor	WW	=	warm water
KB	=	cored hole Ø	STL	=	control line	WWw	=	warm water soft

HOBART



GENERAL INFORMATION



Connections: The connection of the multifunctional braising pan to all services (e.g. electrical, water, drain, exhaust) must comply with all national and local codes of practice and must be carried out by qualified people.

Attention: For systems with a fixed connection, no additional safety device (RCD) is required for TN mains systems in accordance with DIN VDE 0100-410. However, if additional protection is planned on site, an RCD type A with 30 mA (personal protection) or a 300 mA (fire protection) can be used.

Dimensions: Dimensions in the drawing are finished dimensions in Millimeters.

Transport: Minimum measurements of entry doors = outer largest dimension of machine height + 300mm; machine width + 400mm!

Shut-off valves: The Shut-off valves for the multifunctional braising pan must be provided by the customer.

Floor drain: Splash floor drains should be installed for machine cleaning and for general cleaning purpose.

Ventilation: The ventilation and exhaust for the room must be according to VDI 2052. Radiated heat emissions must be considered.

Installation: Installation in accordance to DIN EN 61770.

Machine-Type:				Precipan				Heating: Electrical									
Model:				HBPT 15 HE				Operation: Top									
Capacity:		900 mm		Inner Space:		62 dm ²		Main-Switch: by others									
required supply (by others) (all installations according to local regulations) (technical feasibility must be checked on site)																	
Electrical		Voltage		Frequency		Structure		Fuse		Total Load		Location					
3.7	PA	Equipotential										100mm AFFL					
3.0	EZ	400 V		50/60 Hz		3-N-PE		3 x 80 A		42,3 kW		100mm AFFL					
Water		Consumption		Temp.		Chloride / Chlorine		Hardness		Conductance		Dimension		Connection		Location	
2.0	AW			Drain Approx. 98°C (Siphon provided by customer)								DN50		Drain pipe		100mm AFFL	
1.4	KW	min. 15l/min		max. 23°C								DN20		G ¾ male		100mm AFFL	
1.3	WW			max. 60°C													
Water treatment: Generally we recommend the use of the demineralisation HYDROLINE STEAM CD at> 3°d																	
Flow-Pressure provided <i>min. 1,5 bar / 21,7 psi - max. 6,0 bar / 87,0 psi</i> (above 6,0 bar must be lowered with a pressure reducer, below 1,5 bar need collulting with service)																	
machine-side connentions and data																	
WR = vapors exit / Location: upper edge machine										DA = Steam exit / Location: upper edge machine							
EZ = Power input / Location: lower edge machine						AW = Drain / Location: lower edge machine						KWw/KW / Location: lower edge machine					
Heat-Radiation (thermal output to the room)																	
latent:						16,9 kW						sensibel: 19,0 kW					

Index	Änderungen / Changes	Datum / Date	Name
-------	----------------------	--------------	------

Das Urheberrecht an dieser Zeichnung verbleibt bei der HOBART GmbH.
Jede nicht von uns schriftlich genehmigte Benutzung, Vervielfältigung, Überlassung an Dritte ist strafbar und macht schadensersatzpflichtig.

This document contains proprietary and confidential data of HOBART GmbH. No disclosure, reproduction or use of any part there of may be made without written permission of HOBART GmbH.

HOBART

HOBART GmbH
Robert-Bosch-Straße 17
77656 Offenburg, Germany

Tel.: +49(0)781.600-0
Fax.: +49(0)781.600-2319
www.hobart.de

Datum / Date: 09.02.2024	Project:			
Gezeichnet / Drawn by: N.Hoppner				
Geprüft / Checked by:				
Projectmanager:	Maßstab / Scale: 1:20 @ A3	Order-No.:	Zeichnungsnummer / Drawing-No.:	